

GMC POWERED SLIP ROLLS

Model # PSR-5014, 50" x 14Ga, 1.5 HP, 220V/440V, 3 Phase.....	Sale price: \$4,950.00
Model # PSR-5014-1ph, 50" x 14Ga, 2 HP, 220V, 1 Phase.....	\$5,650.00

Main Features:

- ISO 9001 certified
- Heavy welded all steel construction for maximum rigidity
- Silence electrical motor
- Quick release top roller
- Two rolls are driven
- Precision ground rollers
- 1" roll opening
- All three rolls are made of high grade alloy steel, hardened up to 50 HRC
- All rolls run forward and reverse
- Safety type removable foot pedal
- Overload protection and disconnect switch
- One year warranty for parts

Standard Equipment:

- Electrical cabinet
- Removable safety foot pedal

Specifications	PSR-5016	PSR-5016-1ph	PSR-5014	PSR-5014-1ph
Rolling capacity:				
Mild steel	50" x 16Ga.	50" x 16 Ga.	50" x 14Ga	
Stainless steel	50" x 22Ga.	50" x 20 Ga.	50" x 18 Ga.	
min. thickness capacity	50" x 26Ga.	50" x 26 Ga.	50" x 26 Ga.	
Rolls size, length x dia	50" x 3"	50"x 3"	50"x 3"	
Min. roll bending dia.	3-1/2"	3-1/2"	3-1/2"	
capacity				
Rolls speed	201" / min.	201" / min.	201" / min.	
Rolls opening	1/4"	1/4"	1/4"	
(3) grooves sizes	5/16", 3/8", 1/2"	5/16",3/8", 1/2"	5/16", 3/8", 1/2"	
Main motor	1 HP,220V/440V, 3ph	1.5HP,220V, 1ph	1.5HP,220V, 3ph	2HP,220V,1ph
Net weight	828 LBS	828 LBS	928 LBS	932 LBS
Machine dimensions, LxWxH	68x28x47"	68x28x47"	68x29x48"	68x29x48"

Picture shown PSR-5014

